

Female connector angled, screwable, with 2 LED

PVC, grey, LiYY

Contact assignment

Number of poles	Coding	Rated voltage [V]	Current rating [A]	Cable length = L [m]	Wire cross section [mm²]	Description	Part No.
3	30	3	0,25	2		SAL-8-RKW3-2L-2 / A1	42-10452
				3		SAL-8-RKW3-2L-3 / A1	42-10453
				5		SAL-8-RKW3-2L-5 / A1	42-10454
				10		SAL-8-RKW3-2L-10 / A1	42-10455

TPU, UL, halogenfree, black, Li9Y11Y

3	30	3	0,25	2		SAL-8-RKW3-2L-2 / K1	42-10456
				3		SAL-8-RKW3-2L-3 / K1	42-10457
				5		SAL-8-RKW3-2L-5 / K1	42-10458
				10		SAL-8-RKW3-2L-10 / K1	42-10459

Female connector angled with 3 LED

PVC, grey, LiYY

4	30	3	0,25	2		SAL-8-RKW4-3L-2 / A1	42-10460
				3		SAL-8-RKW4-3L-3 / A1	42-10461
				5		SAL-8-RKW4-3L-5 / A1	42-10462
				10		SAL-8-RKW4-3L-10 / A1	42-10463

TPU, UL, halogenfree, black, Li9Y11Y

4	30	3	0,25	2		SAL-8-RKW4-3L-2 / K1	42-10464
				3		SAL-8-RKW4-3L-3 / K1	42-10465
				5		SAL-8-RKW4-3L-5 / K1	42-10466
				10		SAL-8-RKW4-3L-10 / K1	42-10467