





Female connector angled, screwable
Male connector axial, screwable

PVC, grey, LiYY	Contact assignment	Number of poles	Coding	Rated voltage [V]	Current rating [A]	Cable length = L [m]	Wire cross section [mm²]	Description	Part No.
		3		50 V AC / 60 V DC	3	0,3	0,25	SAL-8-RKW3-RS3-0,3 / A1	42-10149
								SAL-8-RKW3-RS3-0,6 / A1	42-10150
								SAL-8-RKW3-RS3-1,5 / A1	42-10151
								SAL-8-RKW3-RS3-3 / A1	42-10152
		4		50 V AC / 60 V DC	3	0,3	0,25	SAL-8-RKW4-RS4-0,3 / A1	42-10165
								SAL-8-RKW4-RS4-0,6 / A1	42-10166
								SAL-8-RKW4-RS4-1,5 / A1	42-10167
								SAL-8-RKW4-RS4-3 / A1	42-10168

Female connector angled, snap-in
Male connector axial, screwable/snap-in

PVC, grey, LiYY	Contact assignment	Number of poles	Coding	Rated voltage [V]	Current rating [A]	Cable length = L [m]	Wire cross section [mm²]	Description	Part No.
		3		50 V AC / 60 V DC	3	0,3	0,25	SAL-8-RKWS3-RSU3-0,3 / A1	42-10181
								SAL-8-RKWS3-RSU3-0,6 / A1	42-10182
								SAL-8-RKWS3-RSU3-1,5 / A1	42-10183
								SAL-8-RKWS3-RSU3-3 / A1	42-10184
		4		50 V AC / 60 V DC	3	0,3	0,25	SAL-8-RKWS4-RSU4-0,3 / A1	42-10197
								SAL-8-RKWS4-RSU4-0,6 / A1	42-10198
								SAL-8-RKWS4-RSU4-1,5 / A1	42-10199
								SAL-8-RKWS4-RSU4-3 / A1	42-10200