

NICKEL, SCREW TOGETHER HOODS, RAPID ASSEMBLY


DTZK-RA SERIES

TECHNICAL SPECIFICATIONS

| | |
|------------------------|-------------------------------|
| Material: | Zinc, Nickel plated |
| Operating Temperature: | -40°C to +120°C |
| Cable Entry: | Top |
| Thumbscrews: | UNC 4-40 (standard) |
| | M2.5, M2.6 or M3.0 on request |
| Cable Diameter: | From 4.3 mm Up to 13.0 mm |

FEATURES

- Available in sizes 9-15-25-37
- Excellent EMI Shielding
- Re-openable
- Strain relief inserts ensure a secure termination
- Full Metal Jackscrew as standard
- Plastic Cap Jackscrew on request



| Size | Product Code | With Black Plastic Cap J/S | Size | Dim A | Dim B | Dim C |
|--------|--------------|----------------------------|--------|-------|-------|-------|
| 9-way | DTZK9-RA-K | DTZK9-RA-PCBK-K | 9-way | 15,0 | 39,9 | 31,2 |
| 15-way | DTZK15-RA-K | DTZK15-RA-PCBK-K | 15-way | 15,0 | 41,5 | 39,5 |
| 25-way | DTZK25-RA-K | DTZK25-RA-PCBK-K | 25-way | 15,0 | 48,6 | 53,4 |
| 37-way | DTZK37-RA-K | DTZK37-RA-PC-BK-K | 37-way | 15,0 | 53,6 | 69,7 |

BLACK, SCREW TOGETHER HOODS, RAPID ASSEMBLY


DTZK-RA-BK SERIES

TECHNICAL SPECIFICATIONS

| | |
|------------------------|-------------------------------|
| Material: | Zinc, Black |
| Operating Temperature: | -40°C to +120°C |
| Cable Entry: | Top |
| Thumbscrews: | UNC 4-40 (standard) |
| | M2.5, M2.6 or M3.0 on request |
| Cable Diameter: | From 4.3 mm Up to 13.0 mm |

FEATURES

- Available in sizes 9-15-25-37
- Excellent EMI Shielding
- Re-openable
- Strain relief inserts ensure a secure termination
- Full Metal Jackscrew as standard
- Plastic Cap Jackscrew on request



| Size | Product Code | Size | Dim A | Dim B | Dim C |
|--------|----------------|--------|-------|-------|-------|
| 9-way | DTZK9-RA-BK-K | 9-way | 31,2 | 39,9 | 15,0 |
| 15-way | DTZK15-RA-BK-K | 15-way | 39,5 | 41,5 | 15,0 |
| 25-way | DTZK25-RA-BK-K | 25-way | 53,4 | 48,6 | 15,0 |
| 37-way | DTZK37-RA-BK-K | 37-way | 69,7 | 53,6 | 15,0 |