


It's Time to Offer 100% Waterproof Devices...



Specification Specification	
<ul> <li>AB Type</li> <li>Un-mated (Stand-Alone)</li> <li>- IP67 (1M, 30mins): MUC-20PFFR-JS7001</li> <li>- IP68 (1M, 24hrs): MUC-20PFFR-JS8A01</li> <li>- IP68 (5M, 24hrs): MUC-20PFFR-JS8B01</li> <li>- IP68 (10M, 3hrs): MUC-20PFFR-JS8C01</li> </ul>	Current Rating:  -1A for contacts 2, 3 & 4  -1.8A for contacts 1&5 and at the same time 0.5A for contacts 2, 3 & 4
Operating Temperature: -30°C to +85°C	Durability: 10,000 Cycles
• SMT: 255°C/5 Sec.	Connector Size:     SMD 5.52(L) x 8.3(W) x 4.83(H) mm
RoHS Certified	

## Packaging:



Tape Reel

## Applications:



Digital Pressure Monitoring



Night Vision



Tablet PC



Digital Camera and more...



ALTW

For further information please contact the MBS Sales Team

MBS Components Limited Unit L, Tyson Courtyard Weldon South Industrial Estate Corby, Northants NN18 8AZ Tel: 01536 263411 Fax: 01536 268043 Email: sales@mbs-components .com www.mbs-components.com